

## *P-Universal Thinners*

*T 8-18 Fast, T 18-25 Standard, T 25-35 Slow, T 35+ Very Slow*

Field of application	Thinners for all Polaron products.
Chemical bases	Organic solvent blend
General qualities	<p>Do not use in combination with synthetic products.</p> <p>Universal Polaron thinners should be used according to the following temperature ranges:</p> <p>T 8-18 Universal Thinner Fast for: use in cold weather conditions or partial spot repair. It should be used at between 8-18 °C.</p> <p>T 18-25 Universal Thinner Standard for: use in normal weather conditions. It should be used at between 18-25 °C.</p> <p>T 25-35 Universal Thinner Slow for: use in hot weather conditions. It should be used at between 25-35 °C.</p> <p>T 35+ Universal Thinner Very Slow for: use in very hot weather conditions. It should be used above 35°C.</p>
Recommended Products	All Polaron products except synthetic products.
Mixing ratio (volume)	See TDSs for other Polaron products.
Cleaning the equipment	-
Colour	Clear
Storage life	Under normal storage conditions and unopened tins up to 2 years.
Safety	Use suitable respiratory protection (fresh air supply respirator is strongly recommended).



For more detailed information please see Safety Data Sheet.

For professional use only. The technical information in this document has been carefully selected and prepared by us based on the current information. However, these data represent symbolic values. Since application variables are an important factor in product performance, this information should only be presented as a general guide. Polaron assumes no liability or responsibility for the use of this information. Due to any defect / error in this product, only the options of replacing the defective product or refunding the sales price are available, and the right to choose among them belongs to Polaron. See SDS for safety information.