

P-Activator

Field of application	Car-refinish and commercial vehicles top coats and primers
Chemical bases	Special type of additives and solvent mixture
General qualities	<p>P-Activator is an additive that accelerates the drying process of paints, clear coats and primers. This product should be used to accelerate drying in cold weather conditions and minor local repairs.</p> <p>The recommended usage range is 0.1-0.2%. More than the recommended rate should never be used in ovens and hot weather conditions. Excessive use increases the surface tension, matting, capillary perforation, peeling, wrinkling, etc. may cause surface problems such as</p>
Recommended Products	P-Acryl Solid Colour Top Coats, all Polaron Clear Coats and Primers.
Colour	Clear
Storage life	Under normal storage conditions and unopened tins for up to 2 years.
Safety	Use suitable respiratory protection (fresh air supply respirator is strongly recommended).



For more detailed information please see Safety Data Sheet.

For professional use only. The technical information in this document has been carefully selected and prepared by us based on the current information. However, these data represent symbolic values. Since application variables are an important factor in product performance, this information should only be presented as a general guide. Polaron assumes no liability or responsibility for the use of this information. Due to any defect / error in this product, only the options of replacing the defective product or refunding the sales price are available, and the right to choose among them belongs to Polaron. See SDS for safety information.