

# TECHNICAL DATA SHEET



## *Blue Horse 2K Hardener Fast*

Field of application	Car-refinish and commercial vehicles
Chemical bases	Non-yellowing highly durable aliphatic isocyanate resin
General qualities	Blue Horse 2K Hardener Fast use at low temperatures on small medium-sized objects and for partial and spot-repair. It should be used between 8-18 °C
Components	Blue Horse Acrylic Clear Coat, Blue Horse 2K Acrylic Solid Color Top Coats, Blue Horse 4+1 HS 2K Acrylic Primer, Polaron T 8-18/18-25/25-35/35+ Universal Thinners.
Gloss	See info Blue Horse Acrylic Clear Coat
Cleaning the equipment	Universal Acrylic Thinners and Cleaning Thinners
Colour	Clear
Storage life	Under normal storage conditions and unopened tins for up to 1-1.5 years. If the tin is opened, it can be kept for no longer than one week. The tin should be closed immediately after use. Stable approximately one week, depending on temperatures and humidity.
Safety	Use suitable respiratory protection (fresh air supply respirator is strongly recommended).



For more detailed information please see Safety Data Sheet.

For professional use only. The technical information in this document has been carefully selected and prepared by us based on the current information. However, these data represent symbolic values. Since application variables are an important factor in product performance, this information should only be presented as a general guide. Polaron assumes no liability or responsibility for the use of this information. Due to any defect / error in this product, only the options of replacing the defective product or refunding the sales price are available, and the right to choose among them belongs to Polaron. See SDS for safety information.